



[SPECIFICATION]

1. OPERATING VOLTAGE : DC 24V
2. WATTAGE : 150W
3. LUMINOUS : 10000 lm
4. LED : CREE XPG WHT-R4
5. BEAM ANGLE : 10, 25, 40, 60
6. OPERATING TEMPERATURE : -40°C ~ 50°C  
AC Type : 50,000 (Hr)  
DC Type : 30,000 (Hr)
7. LIFE TIME : 50,000 (Hr)
8. IP RATING : IP68 (SMPS-IP65)

NO.	PART NO.	DESCRIPTION	Q'TY
01	TOP COVER	ALUMINUM	1EA
02	REFLECTOR	PC	1EA
03	BOLT	M4*18L / SUS	12EA
04	WINDOW	PC (natural)	1EA
05	BRACKET	PO	1EA
06	INJECTION BOLT	M8*20L / SUS	6EA
07	BUSHING	ø23.0 * 4t	6EA
08	BODY	ALUMINUM	1EA
09	CONNECTOR	3Pin CONNECTOR	1EA
10	SMPS	CLG-150 / 3Pin CONNECTOR(Female)	3SET
11	BOLT	M4*8L / SUS	4EA
—	ACCESSORY	1/2" x40 HEX BOLT,NUT,WASHER	

REV. ZONE	REVISION RECORD
ANGLE	
UNIT	mm SCALE 1:1
SHEET	1/1 REV P2
Q'ty	1 SIZE A0
DESIGN : K.D.H	DATE 11.11.24
CHECKED : K.D.H	DATE
APPROVAL : K.D.H	DATE
WEIGHT : 5.6kg (SMPS-RI(2))	
FINISH : 亜鉛めっき	
MATERIAL : 鋁合金	
CODE NO. : 0000	
PART NAME : SPEC	
MODEL NAME : P1T MASTER 30 (AC Type)	

