



- *SPECIFICATION**
1. OPERATING VOLTAGE (12V) : DC11.0V ~ 16.0V
(24V) : DC18.0V ~ 32.0V
 2. LED : 3W(750mA)
 3. REFLECTOR : PC / VACUUM METALLIZED
 4. LENS : ACRYLIC
 5. VIBRATION : 8.6G_{RMS}
 6. WEATHER PROOF & DUST RESISTANCE
 7. TEMPERATURE : -40℃~105℃
 8. LIFE : 500,000Hrs
 9. IP RATING : IP67
 10. TENSILE STRENGTH: THE WIRES CAN WITHSTAND ABOUT 15Kg PULL FOR 3SEC.

LED QUANTITY	WATT(W)	A (inch/mm)	B (inch/mm)	C (inch/mm)	D (inch/mm)	BRACKET #1/#2 (PCS)	WEGHT (Kg)
16 LED	48	5.8(147.6)	4.7 (120.0)	3.0(76.25)	*	2 / 1	1.45
24 LED	72	7.8(198.4)			*		1.90
40 LED	120	11.8(300.0)	4.7 (120.0)	3.0(76.25)	4.92(125)	8 / 4	2.20
80 LED	240	21.7(550.0)			5.0(127.8)		5.05
120 LED	360	31.8(808.0)			8.35(212)		7.65

UNIT	mm	DRAWING	CHECK	APPROVAL	TITLE	DOUBLE STACK XMITTER LED LIGHT BAR
SCALE	2:1					
CREATED	2008.05.28					
[VX] Vision X					DRAWING NO	VX-TS-XMITTERDBL